

Date Prepared : 05/28/2004 SDS No : 358NVOC Date Revised : 08/21/2017 Revision No : 4

# Qualitek® No Clean 358NVOC Flux

# 1. PRODUCT AND COMPANY IDENTIFICATION

# **PRODUCT NAME:** Qualitek® No Clean 358NVOC Flux **PRODUCT DESCRIPTION:** No Clean VOC Free Flux

# MANUFACTURER

Qualitek International, Inc. 315 Fairbank St. Addison, IL 60101 Emergency Phone: (800) 535-5053 Customer Service: (630) 628-8083

# 24 HR. EMERGENCY TELEPHONE NUMBERS

1-800-535-5053 Infotrac 1-352-323-3500 Outside the U.S.

### 2. HAZARDS IDENTIFICATION

#### **GHS CLASSIFICATIONS**

#### Health:

Skin Irritation, Category 2

## **GHS LABEL**



### SIGNAL WORD: WARNING

### HAZARD STATEMENTS

H315: Causes skin irritation.

### **PRECAUTIONARY STATEMENT(S)**

#### **Prevention:**

P302+P352: IF ON SKIN: Wash with plenty of water/... P332+P313: If skin irritation occurs: Get medical advice/attention.

## POTENTIAL HEALTH EFFECTS

**EYES:** May cause eye irritation.

SKIN: Frequent or prolonged contact may irritate the skin and cause a skin rash (dermatitis).

**INGESTION:** May cause irritation of the mouth, throat, and gastrointestinal tract.

**INHALATION:** May be irritating to the mucous membranes and to the respiratory tract.

CARCINOGENICITY: This product contains no components at concentrations of 0.1 percent or greater that are

CAS

25498-49-1

111-76-2

# SAFETY DATA SHEET



Date Prepared : 05/28/2004 SDS No: 358NVOC Date Revised : 08/21/2017 **Revision No:** 4

< 5

< 5

# **Qualitek® No Clean 358NVOC Flux**

listed by IARC, NTP, OSHA or ACGIH as carcinogens.

# 3. COMPOSITION / INFORMATION ON INGREDIENTS **Chemical Name** Wt.% **Butyl** Cellusolve

# 4. FIRST AID MEASURES

Glycol Ether TPM

**EYES:** Remove any contact lenses. Immediately flush eyes with large quantities of water for at least 15 minutes. Get medical attention if irritation or vision problems develop.

**SKIN:** Immediately wash skin with soap and copious amounts of water. Remove any contaminated clothing. Get medical attention if irritation develops. Wash contaminated clothing before reuse.

**INGESTION:** If swallowed, DO NOT induce vomiting. Keep at rest. Get prompt medical attention.

**INHALATION:** Move person to fresh air. If breathing is stopped or is labored, give assisted respiration (e.g. mouthto-mouth). Supplemental oxygen may be indicated. Seek medical advice if necessary.

# SIGNS AND SYMPTOMS OF OVEREXPOSURE

EYES: Stinging, tearing, redness and swelling.

SKIN: Redness, burning, drying, cracking and rash.

**INGESTION:** Possible nausea and/or vomiting

**COMMENTS:** If victims of chemical over-exposure are taken for medical attention, give a copy of the label or this SDS to the physician/health care professional.

# 5. FIRE FIGHTING MEASURES

**EXTINGUISHING MEDIA:** Use media for surrounding fire conditions.

FIRE FIGHTING PROCEDURES: Cool containers with water to prevent rupturing.

FIRE FIGHTING EQUIPMENT: Self contained breathing apparatus and full protective turn-out gear.

## 6. ACCIDENTAL RELEASE MEASURES

SMALL SPILL: Absorb spilled material with sand or other noncombustible absorbent material and place into containers for later reclamation or disposal.

LARGE SPILL: Contain spilled liquid with sand, absorbent material, or concrete dikes for recovery or disposal. Collect spilled material for disposal in accordance with all applicable Federal, State and Local regulations.

# **ENVIRONMENTAL PRECAUTIONS**

WATER SPILL: Contain spill. Prevent contact wth eyes, skin and clothing. Prevent flow to larger or flowing



Date Prepared : 05/28/2004 SDS No : 358NVOC Date Revised : 08/21/2017 Revision No : 4

# Qualitek® No Clean 358NVOC Flux

bodies of water. Isolate and take up material for recovery or disposal.

LAND SPILL: In the event of a land spill, prevent liquid from entering sewers, watercourses, or low areas.

# 7. HANDLING AND STORAGE

**HANDLING:** Use appropriate personal protective equipment, and handle in a well-ventilated area. Handle and use in a manner consistent with good industrial/manufacturing techniques and practices.

**STORAGE:** Store in a cool, well ventilated place away from incompatible materials. Keep containers tightly closed when not in use. Protect containers from damage.

**ELECTROSTATIC ACCUMULATION HAZARD:** Use proper grounding and bonding procedures when transferring material.

# 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

**ENGINEERING CONTROLS:** Provide general and/or local exhaust ventilation to control airborne levels below the OSHA/ACGIH exposure guidelines.

# PERSONAL PROTECTIVE EQUIPMENT

EYES AND FACE: Wear splash goggles or glasses with face shield.

SKIN: Neoprene rubber gloves, impermeable gloves, cuffed butyl-rubber gloves, or nitrile rubber gloves.

**RESPIRATORY:** Atmospheric levels should be maintained below the exposure guideline. For most conditions, no respiratory protection should be needed; however, if handling at elevated temperatures and/or without sufficient ventilation, use a NIOSH/MSHA approved air-purifying respirator.

**PROTECTIVE CLOTHING:** Protective clothing and safety shoes as necessary to minimize contact.

**WORK HYGIENIC PRACTICES:** Good personal hygiene practices should be used. Wash after any contact, before eating, and at the end of the work period.

OTHER USE PRECAUTIONS: Eye wash station and quick drench safety shower in immediate work area.

# 9. PHYSICAL AND CHEMICAL PROPERTIES

ODOR: Slight acidic odor. APPEARANCE: Liquid COLOR: Dark amber. FLASH POINT AND METHOD: Not Flammable FLAMMABLE LIMITS: N/A VAPOR PRESSURE: 218 mmHg at 78°C (173°F) VAPOR DENSITY: 0.6 (Air=1) BOILING POINT: 105°C (221°F)



Date Prepared : 05/28/2004 SDS No : 358NVOC Date Revised : 08/21/2017 Revision No : 4

# Qualitek® No Clean 358NVOC Flux

MELTING POINT: Not Applicable

SOLUBILITY IN WATER: Complete

**EVAPORATION RATE:** < 1.0 (n-Butyl Acetate=1)

SPECIFIC GRAVITY: 0.994 to 1.006

**10. STABILITY AND REACTIVITY** 

HAZARDOUS POLYMERIZATION: Will not occur.

**STABILITY:** Stable under ordinary use and storage conditions.

HAZARDOUS DECOMPOSITION PRODUCTS: None known.

**INCOMPATIBLE MATERIALS:** Strong bases and strong oxidizing materials.

## **11. TOXICOLOGICAL INFORMATION**

GENERAL COMMENTS: No toxicological information available at this time.

## **12. ECOLOGICAL INFORMATION**

GENERAL COMMENTS: No information on ecological toxicity or biodegradability is available at this time.

## **13. DISPOSAL CONSIDERATIONS**

**DISPOSAL METHOD:** Dispose of this material, contaminated absorbent material and other contaminated materials in an approved waste disposal facility, according to all applicable Federal, State, and Local regulations. Recovery and reuse, rather than disposal, should be the ultimate goal in handling efforts.

**EMPTY CONTAINER:** Empty drums should be completely drained, properly bunged and promptly returned to a drum reconditioner, or otherwise properly disposed of.

## **14. TRANSPORT INFORMATION**

## DOT (DEPARTMENT OF TRANSPORTATION)

**PROPER SHIPPING NAME:** Not regulated by DOT

## **15. REGULATORY INFORMATION**

### **UNITED STATES**

## SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT)

311/312 HAZARD CATEGORIES: Not considered a hazard.

# CERCLA (COMPREHENSIVE RESPONSE, COMPENSATION, AND LIABILITY ACT)

**CERCLA REGULATORY:** Not subject to any special reporting under the requirements of the Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA).



Date Prepared : 05/28/2004 SDS No : 358NVOC Date Revised : 08/21/2017 Revision No : 4

# Qualitek® No Clean 358NVOC Flux

# TSCA (TOXIC SUBSTANCE CONTROL ACT)

**TSCA STATUS:** All ingredients are listed or are exempt from listing (as polymers) on the Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

**CALIFORNIA PROPOSITION 65:** When used for soldering and similar applications chemicals may be produced which are known to some states to cause birth defects or other reproductive harm.

## **16. OTHER INFORMATION**

**REASON FOR ISSUE:** New format

APPROVED BY: P. Han TITLE: Technical Director

PREPARED BY: J. Saleda-Layton Date Revised: 08/21/2017

**INFORMATION CONTACT:** (630) 628-8083

**REVISION SUMMARY:** This SDS replaces the 04/29/2014 SDS. Revised: Section 1: REASON FOR ISSUE.

HMIS RATING	1
FLAMMABILITY	0
PHYSICAL HAZARD	0
PERSONAL PROTECTION	С

MANUFACTURER DISCLAIMER: The information contained herein is based upon data considered to be accurate and is offered solely for information, customer consideration and investigation. The manufacturer extends no warranties, makes no representations and assumes no responsibility as to the accuracy, completeness or suitability of this data for any purchaser's use. The content of this Safety Data Sheet relates only to this product as sold and does not relate to use with any other material or in any process. All chemical products should be used only by, or under, the direction of technically qualified personnel, who are aware of the hazards involved and of the necessity for reasonable care in handling. Hazard communication regulations, United States Occupational Health and Safety (OSHA) and Canadian Workplace Hazardous Materials Information System (WHMIS) require that employees must be trained in the use of Safety Data Sheets as a source of hazards information and response.