



QUALITEK®

35 Defoamer

DESCRIPTION

35 Defoamer is a non-ionic surfactant that will reduce foam in aqueous cleaning operations.

APPLICATION

35 Defoamer may be used in cleaning applications where foaming is excessive. It is recommended to add 5-6 capfuls to the wash operations to reduce the amount of foam. Additions of 1-4 capfuls may be required periodically (every 4-8 hours) to keep the foam level down. This product works optimally in a water wash at 140°F – 150°F. 35 Defoamer may also be applied by spraying. Simply spray 35 Defoamer onto several boards before they enter the wash operation. This should reduce foaming in the wash zone for several hours. While 35 Defoamer is designed not to harm resin beds in closed loop systems, it will be more likely filtered out, and more or/frequent amount may be required in such cases.

PHYSICAL & CHEMICAL CHARACTERISTICS

Color and Appearance	Clear
pH (as is)	4.43
Specific Gravity @24°C	1.020
Flash Point	None
Shelf life (un-opened)	2 years from (DOM)

PACKAGING & STORAGE

35 Defoamer is available in 1, 5 and 55 gallon containers. It should be stored in cool, dry place.

Qualitek ® is a trademark of Qualitek International, Inc.

TEL: (630) 628-8083 FAX: (630) 628-6543 E-MAIL: solder@qualitek.com HOME PAGE:<http://www.qualitek.com>

HEADQUARTERS: 315 Fairbank St., Addison, IL 60101 U.S.A.

WORLDWIDE BRANCHES: UNITED KINGDOM – CHINA – PHILLIPINES - SINGAPORE

QUALITEK INTERNATIONAL, INC.

AN ISO 9001:2008 CERTIFIED COMPANY

This data is based on information that the manufacturer believed to be reliable and offered in good faith. Qualitek International, Inc. makes no warranties expressed or implied as to its accuracy and assumes no responsibilities and liabilities arising out of its use by others as conditions and methods of use of the products is beyond the control of Qualitek International, Inc. The user must determine the suitability of the product before using it on a commercial basis. The warranties extend only to the conformity of the product to the physical descriptions. In no event will Qualitek International, Inc. be responsible for special, incidental and consequential damages whether the claim is in contract, negligence or otherwise.

Rev: 051011-35Defoamer

Consult MSDS for health and safety information