



# QUALITEK®

## 820 Flux Water-Soluble, Halide Free

### DESCRIPTION

820 is a halogen free, water-soluble organic flux. 820 provides a stable head of tight bubbles in foaming applications. The flux residues are removed easily in warm water.

### BENEFITS

- Halide-Free
- Excellent wetting on virtually all types of substrates
- Remains active at high temperatures

### APPLICATION METHODS

820 lends itself particularly well to foaming applications, and may also be applied by dip, spray, or brush methods. 820 provides a rapid break-up of bubbles that evenly coat the board surface. Should the flux become too concentrated due to solvent loss, add Qualitek 800 thinner to maintain the proper specific gravity and performance.

### PHYSICAL & CHEMICAL CHARACTERISTICS

<b>Color and Appearance</b>	Light Amber Liquid
<b>Solids Content, % (By Wt.)</b>	25.0 – 29.0
<b>Specific Gravity</b>	0.865 +/- 0.006
<b>Flash Point</b>	53°F
<b>pH (as is)</b>	7.8 – 8.8
<b>Flux Classification per J-STD-004</b>	ORM0
<b>Shelf life (un-opened)</b>	2 years

### RESIDUE REMOVAL

As with all water-soluble fluxes, post cleaning is required. Residues can be easily removed with both hot and cold water, thus; no neutralizer is needed. De-ionized water should be used in the final rinse for cleanliness results beyond MIL-28809A.

### PACKAGING & STORAGE

820 flux is available in 1, 5 and 55 gallon containers. It should be stored in cool, dry place away from ignition sources.

**Qualitek® is a trademark of Qualitek International, Inc**

TEL: (630) 628-8083 FAX: (630) 628-6543 E-MAIL: [solder@qualitek.com](mailto:solder@qualitek.com) HOME PAGE: <http://www.qualitek.com>

HEADQUARTERS: 315 Fairbank St., Addison, IL 60101 U.S.A.

WORLDWIDE BRANCHES: UNITED KINGDOM – MEXICO – CHINA – PHILLIPINES – SINGAPORE

**QUALITEK INTERNATIONAL, INC. AN ISO 9002 CERTIFIED COMPANY**

This data is based on information that the manufacturer believed to be reliable and offered in good faith. Qualitek International, Inc. makes no warranties expressed or implied as to its accuracy and assumes no responsibilities and liabilities arising out of its use by others as conditions and methods of use of the products is beyond the control of Qualitek International, Inc. The user must determine the suitability of the product before using it on a commercial basis. The warranties extend only to the conformity of the product to the physical descriptions. In no event will Qualitek International, Inc. be responsible for special, incidental and consequential damages whether the claim is in contract, negligence or otherwise.

Rev: 080499-820

Consult MSDS for health and safety information