

**Date Prepared:** 01/09/2014

SDS No : SK #45

**Date Revised:** 08/21/2017

**Revision No:** 2

## Qualitek® SK #45

## 1. PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: Qualitek® SK #45

PRODUCT DESCRIPTION: Stencil Kleener

## **MANUFACTURER**

Qualitek International, Inc.

315 Fairbank St.

Addison, IL 60101

**Emergency Phone:** (800) 535-5053 **Customer Service:** (630) 628-8083

## 24 HR. EMERGENCY TELEPHONE NUMBERS

1-800-535-5053 Infotrac

1-352-323-3500 Outside the U.S.

## 2. HAZARDS IDENTIFICATION

#### **GHS CLASSIFICATIONS**

#### Health:

Eye Irritation, Category 2B

## **GHS LABEL**



Exclamation mark

SIGNAL WORD: WARNING

#### HAZARD STATEMENTS

H227: Combustible liquid.

H320: Causes eye irritation.

H302: Harmful if swallowed.

## PRECAUTIONARY STATEMENT(S)

#### **Response:**

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.

## **Storage:**

P404: Store in a closed container.

## Disposal:



**Date Prepared:** 01/09/2014

**SDS No :** SK #45 **Date Revised :** 08/21/2017

**Revision No:** 2

## Qualitek® SK #45

P501: Dispose of contents/container in accordance to local/regional/national/international regulations.

## POTENTIAL HEALTH EFFECTS

**EYES:** May cause eye irritation.

**SKIN:** Frequent or prolonged contact may irritate the skin and cause a skin rash (dermatitis).

**INGESTION:** Minimal toxicity. Small amounts of the liquid aspirated into the respiratory system during

ingestion, or from vomiting, may cause bronchiopneumonia or pulmonary edema.

**INHALATION:** May be irritating to the mucous membranes and to the respiratory tract.

**CARCINOGENICITY:** This product contains no components at concentrations of 0.1 percent or greater that are listed by IARC, NTP, OSHA or ACGIH as carcinogens.

## 3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	Wt.%	CAS
Glycol Ether PNP	< 70	1569-01-3
Ethoxypropanol	< 10	1569-02-4
Methoxypropanol	< 10	107-98-2

### 4. FIRST AID MEASURES

**EYES:** Remove any contact lenses. Immediately flush eyes with large quantities of water for at least 15 minutes. Get immediate medical attention.

**SKIN:** Immediately flush with large amounts of water. Use soap if available. Remove contaminated clothing, including shoes, after flushing has begun. Get medical attention as soon as possible.

**INGESTION:** If swallowed, DO NOT induce vomiting. Keep at rest. Get prompt medical attention.

**INHALATION:** Using proper respiratory protection, immediately remove the affected victim from exposure. Administer artificial respiration if breathing is stopped. Keep at rest. Call for prompt medical attention.

**COMMENTS:** If victims of chemical over-exposure are taken for medical attention, give a copy of the label or this SDS to the physician/health care professional.

## 5. FIRE FIGHTING MEASURES

**EXTINGUISHING MEDIA:** Carbon dioxide or dry chemical for small fires. Foam (alcohol, polymer, or ordinary) and water fog for large fires.

**FIRE FIGHTING PROCEDURES:** Cool containers with water to prevent rupturing.

**FIRE FIGHTING EQUIPMENT:** Self contained breathing apparatus and full protective turn-out gear.

## 6. ACCIDENTAL RELEASE MEASURES



**Date Prepared:** 01/09/2014

**SDS No :** SK #45 **Date Revised :** 08/21/2017

**Revision No:** 2

## Qualitek® SK #45

**SMALL SPILL:** Absorb spilled material with sand or other noncombustible absorbent material and place into containers for later reclamation or disposal.

**LARGE SPILL:** Contain spilled liquid with sand, absorbent material, or concrete dikes for recovery or disposal. Collect spilled material for disposal in accordance with all applicable Federal, State and Local regulations.

## **ENVIRONMENTAL PRECAUTIONS**

**WATER SPILL:** Contain spill. Prevent contact wth eyes, skin and clothing. Prevent flow to larger or flowing bodies of water. Isolate and take up material for recovery or disposal.

**LAND SPILL:** In the event of a land spill, prevent liquid from entering sewers, watercourses, or low areas.

## 7. HANDLING AND STORAGE

**HANDLING:** Keep container closed. Handle and open containers with care. DO NOT handle near an open flame, heat, or other sources of ignition. DO NOT pressurize, cut, heat, or weld containers. Empty product containers may contain product residue. DO NOT reuse empty containers without commercial cleaning or reconditioning.

**STORAGE:** Store in a cool, well ventilated place away from incompatible materials. Keep containers tightly closed when not in use. Protect containers from damage.

**ELECTROSTATIC ACCUMULATION HAZARD:** Use proper grounding and bonding procedures when transferring material.

#### 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

**ENGINEERING CONTROLS:** Provide general and/or local exhaust ventilation to control airborne levels below the OSHA/ACGIH exposure guidelines.

## PERSONAL PROTECTIVE EQUIPMENT

**EYES AND FACE:** Wear splash goggles or glasses with face shield.

**SKIN:** Neoprene rubber gloves, impermeable gloves, cuffed butyl-rubber gloves, or nitrile rubber gloves.

**RESPIRATORY:** Atmospheric levels should be maintained below the exposure guideline. For most conditions, no respiratory protection should be needed; however, if handling at elevated temperatures and/or without sufficient ventilation, use a NIOSH/MSHA approved air-purifying respirator.

**PROTECTIVE CLOTHING:** Protective clothing and safety shoes as necessary to minimize contact.

**WORK HYGIENIC PRACTICES:** Good personal hygiene practices should be used. Wash after any contact, before eating, and at the end of the work period.

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

**ODOR:** Mild ether-like odor

**APPEARANCE:** Colorless liquid

**pH:** 5.5 to 6.5



**Date Prepared:** 01/09/2014

**SDS No :** SK #45 **Date Revised :** 08/21/2017

Revision No: 2

## Qualitek® SK #45

FLASH POINT AND METHOD: Not Flammable

FLAMMABLE LIMITS: 0% to 0%

**BOILING POINT:** 140°C (284°F) to 160°C (320°F)

**MELTING POINT:** Not Applicable

**SPECIFIC GRAVITY:** 0.885 to 0.915 g/cc at 25°C

## 10. STABILITY AND REACTIVITY

**HAZARDOUS POLYMERIZATION:** Will not occur under normal use and storage conditions.

**STABILITY:** Stable under ordinary use and storage conditions.

**HAZARDOUS DECOMPOSITION PRODUCTS:** None known.

**INCOMPATIBLE MATERIALS:** Strong bases and strong oxidizing materials.

## 11. TOXICOLOGICAL INFORMATION

**GENERAL COMMENTS:** No toxicological information available at this time.

#### 12. ECOLOGICAL INFORMATION

**GENERAL COMMENTS:** No information on ecological toxicity or biodegradability is available at this time.

#### 13. DISPOSAL CONSIDERATIONS

**DISPOSAL METHOD:** Dispose of this material, contaminated absorbent material and other contaminated materials in an approved waste disposal facility, according to all applicable Federal, State, and Local regulations. Recovery and reuse, rather than disposal, should be the ultimate goal in handling efforts.

**EMPTY CONTAINER:** Empty drums should be completely drained, properly bunged and promptly returned to a drum reconditioner, or otherwise properly disposed of.

## 14. TRANSPORT INFORMATION

**DOT (DEPARTMENT OF TRANSPORTATION)** 

**PROPER SHIPPING NAME:** Not regulated by DOT

# 15. REGULATORY INFORMATION

## UNITED STATES

SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT)

311/312 HAZARD CATEGORIES: Acute health and chronic health hazard.

CERCLA (COMPREHENSIVE RESPONSE, COMPENSATION, AND LIABILITY ACT)

**CERCLA REGULATORY:** Not subject to any special reporting under the requirements of the Comprehensive



**Date Prepared:** 01/09/2014

**SDS No :** SK #45 **Date Revised :** 08/21/2017

**Revision No: 2** 

## Qualitek® SK #45

Environmental Response, Compensation, and Liability Act (CERCLA).

## TSCA (TOXIC SUBSTANCE CONTROL ACT)

**TSCA STATUS:** All ingredients are listed or are exempt from listing (as polymers) on the Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

**CALIFORNIA PROPOSITION 65:** When used for soldering and similar applications chemicals may be produced which are known to some states to cause birth defects or other reproductive harm.

## 16. OTHER INFORMATION

**REASON FOR ISSUE:** New format

**APPROVED BY:** P. Han **TITLE:** Technical Director

**PREPARED BY:** J. Saleda-Layton **Date Revised:** 08/21/2017

**INFORMATION CONTACT:** (630) 628-8083

**REVISION SUMMARY:** This SDS replaces the 05/05/2015 SDS.

### **HMIS RATING**



MANUFACTURER DISCLAIMER: The information contained herein is based upon data considered to be accurate and is offered solely for information, customer consideration and investigation. The manufacturer extends no warranties, makes no representations and assumes no responsibility as to the accuracy, completeness or suitability of this data for any purchaser's use. The content of this Safety Data Sheet relates only to this product as sold and does not relate to use with any other material or in any process. All chemical products should be used only by, or under, the direction of technically qualified personnel, who are aware of the hazards involved and of the necessity for reasonable care in handling. Hazard communication regulations, United States Occupational Health and Safety (OSHA) and Canadian Workplace Hazardous Materials Information System (WHMIS) require that employees must be trained in the use of Safety Data Sheets as a source of hazards information and response.