

1. Product Identification

Product Code	351 NVOC No Clean Flux		
Trade Name	None		
Manufacturer	Qualitek-Europe Ltd	Unit 9 Apex court, Bassendale Road. Bromborough, Wirral. CH62 3RE UK Tel 44(0) 151-334-0888 Fax 44(0)151-346-1408	
Supplier / Importer			
24 hour Emergency Contact (UK)	0151-334-0888		

2. Composition and information on Components

Hazardous Components	Content	EC No	CAS	Hazard	Risk
Not Classified Organic Acids	5%	n/a	n/a	X _i :Irritant	R36/37/38
Remainder				Not classified	

3. Hazard Identification

Main Hazards	May cause irritation to eyes and skin
Health Effects Inhalation - Ingestion	Inhalation of soldering fumes or ingestion may cause headache, nausea, muscular pain. Irritation of the eyes and nose may result from contact with soldering fumes.
Chronic (Prolonged effects)	Anaemia, insomnia, weakness, constipation, nausea and abdominal pain due to ingestion. Skin rash, damage of mucous membrane due to skin exposure and inhalation.

4. First Aid Measures

First Aid - Eyes	Immediately flush the eyes with water for at least 15 minutes, holding the eye open. Obtain medical attention urgently.
First Aid - Skin	Wash thoroughly with soap and water and remove all contaminated clothing as washing proceeds. Apply suitable lotion to prevent dryness. Seek medical attention.
First Aid - Inhalation	Remove person to fresh air and keep subject warm and at rest. Seek medical attention.
First Aid - Ingestion	Wash out mouth with water. Do not induce vomiting. Keep subject warm and at rest. Seek medical attention.

5. Fire Fighting Measures

Extinguishing media	This product is not flammable. However similar products which are flammable may also be in the vicinity. Therefore the use of Carbon Dioxide, Dry chemical, Alcohol resistant foam is recommended. Beware of the possibility of re-ignition of other flammable products in the vicinity.
Special Hazards	This product is not regarded as hazardous.
Protective Equipment for Fire Fighting	Wear full protective clothing and use breathing apparatus.

6. Accidental Release Measures

Personal Precautions	Wear appropriate protective clothing. Eliminate sources of ignition. Avoid breathing vapour.
Environmental Precautions	Try to prevent the product entering drains or water courses.
Spillages	Small spillages can be flushed with large volumes of water. Larger spillages should be collected for disposal. Allow to evaporate if it is safe to do so or contain using absorbent material such as earth, sand or other inert material.

7. Handling and Storage

Handling	Use in well ventilated area. Avoid breathing in vapour, mist or resultant soldering fumes. Avoid contact with eyes, skin and clothing. Keep container tightly closed. Larger containers (20l) are heavy. Take care when lifting and pouring.
Storage	Storage area should be well ventilated, cool and dry. Store in original containers. Re package only if container becomes damaged. Store away from sources of heat or ignition.

8. Exposure Controls - Personal Protection

Occupational Exposure Limits 351NVOC	TLV n/a	OSHA PEL n/a	ACGHIH TLV n/a
note that although there are no limits for this product, limits may exist fumes of soldering process and these must be adhered to.			
Engineering Control Measures	Ensure work area is well ventilated and equipment exhausted. If pouring is needed then this should be arranged so as not to expose the operator to unnecessary vapour levels.		
Respiratory Protection	Respiratory protection if there is a risk of exposure to high vapour levels.		
Hand protection	Nitrile rubber gloves or PVC gloves should be used when handling or pouring		
Eye Protection	Close fitting Chemical goggles should be worn when handling or pouring.		
Skin Protection	Normal work wear but rubber apron if there is a danger of splashing or spillage.		
Foot Protection	Wear protective boots or toe caps when handling drums.		

9. Physical and Chemical Properties

Appearance	Clear colourless liquid	
Odour	Ethereal Odour	
pH (as is)	3.5	
Boiling point	100 Deg C @ 760mm Hg	
Melting point	0 Deg C	
Flash Point	none	
Auto Ignition Temperature	none	
Flammability limits in air	Lower :	none
	Upper :	none
Explosion Limits	Lower :	none
	Upper :	none
Vapour Density	n/a	(Air = 1)
Evaporation Rate	<1	(BuAc = 1)
Specific Gravity	1.050 +/- 0.004	(H ₂ O = 1 @ 25 Deg C)
Solubility	Completely soluble in water	

10. Stability and Reactivity

Stability	Stable under normal conditions
Conditions to avoid	High temperature - sources of ignition
Materials to avoid	Strong oxidising agents
Hazardous Decomposition Products	May release toxic vapours / gases such as Carbon Monoxide, Carbon Dioxide

11. Toxicological Information

Basis of Assessment	The constituents of this product are regarded as non toxic and there are no published limits for the following :
Acute Toxicity - Oral	n/a
Acute Toxicity - Dermal	n/a
Acute Toxicity - Inhalation	n/a
Eye Irritation	Irritant
Skin Irritation	Slight Irritant
Respiratory Irritation	Possible Irritant
Skin sensitisation	May cause skin sensitisation
(Sub) Chronic Toxicity	no data available
Human effects	no data available

12. Ecological Information

Mobility	The product will readily dissolve in water
Degradability	The product is readily Biodegradable
Bio-accumulation	Not expected to accumulate
Ecotoxicity	Poses little risk of oxygen depletion in aquatic systems

13. Disposal

Product	Material is classified as special waste under the COPA regulations 1980 and must be disposed of in accordance with those regulations.
Containers	Leave labels in tact until containers have been thoroughly cleaned. Empty containers may contain hazardous residues and vapours. Dispose of containers with care.

